



- PHYSICAL CHARACTERISTICS:
- 1- CORROSION RESISTANT METAL END CAPS.
  - 2- CORK GASKETS (STD).
  - 3- CORROSION RESISTANT CENTERTUBE.
  - 4- WATER ABSORBING MEDIA
  - 5- MAXIMUM OPERATING TEMPERATURE IS 250° F.
  - 6- 100 PSI COLLAPSE STRENGTH.
  - 7- BETA 10 > 200

THE INFORMATION AND DATA CONTAINED HEREIN  
CONFORMS TO  
ASME Y14.5-M 1994

DRAWING  
STATUS

**PRODUCTION**

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION  
AND SUCH INFORMATION MAY NOT BE DISCLOSED TO  
OTHERS OR USED FOR ANY PURPOSE WITHOUT WRITTEN  
PERMISSION FROM THE HILLIARD CORP.  
© COPYRIGHT THE HILLIARD CORPORATION,  
ALL RIGHTS RESERVED

UNLESS OTHERWISE SPECIFIED  
FINISH:  POLISHED  UNFINISHED

UNLESS OTHERWISE SPECIFIED  
BREAK CORNERS:  CHAMFERED  MAX

UNLESS OTHERWISE SPECIFIED  
FRACTIONAL DIMENSIONS - 1/16  
DECIMAL DIMENSIONS - .015  
ANGLES - 30°

MADE FROM

THE HILLIARD CORPORATION  
100 WEST FORTYTH STREET  
ELMHURST, NEW YORK 11003

PROPORTIONS ARE AS SHOWN  
(1) DIMENSIONS IN IN

DRAWN	BY	DATE
ROC	ROC	01/06/09
CHECKED	BY	DATE
LTH	LTH	01/06/09
APPROVED	BY	DATE
LTH	LTH	01/06/09
SIMILAR TO:		
SCALE: NTS		

TITLE	SHEET 1	DD-700-274	C
FGX630-00-C DATA SHEET	OF 1		