



PHYSICAL CHARACTERISTICS:

1. CORROSION RESISTANT METAL END CAPS.
2. MAX. OPERATING TEMP. IS 250° F.
3. MAXIMUM RECOMMENDED DIFFERENTIAL = 20 PSID
4. VITON O-RING
5. INSIDE/OUTSIDE FLOW
6. BETA 40 > 200

THE INFORMATION AND DATA CONTAINED HEREIN
CONFORMS TO
ASME Y14.5-M 1994

DRAWING
STATUS

PRODUCTION

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION
AND SUCH INFORMATION MAY NOT BE DISCLOSED TO
OTHERS OR USED FOR ANY PURPOSE WITHOUT WRITTEN
PERMISSION FROM THE HILLIARD CORP.
© COPYRIGHT THE HILLIARD CORPORATION,
ALL RIGHTS RESERVED

UNLESS OTHERWISE SPECIFIED
FINISH: UNLESS OTHERWISE SPECIFIED
BREAK CORNERS: RXX
UNLESS OTHERWISE SPECIFIED:
FRACTIONAL: - 1/16
DECIMALS: - 0.005
HOLE: - 0.015

MADE FROM

THE HILLIARD CORPORATION
100 WEST FOURTH STREET
ELMHURST, NEW YORK 11402

DRAWN	BY	DATE
ROC		04/20/13
CHECKED	BY	DATE
LTH		4/22/13
APPROVED	BY	DATE
LTH		4/22/13
SIMILAR TO:		
SCALE: 3/4		

TITLE	DATA SHEET 3860-05-043	SHEET 1 OF 1	DD-700-520	C